

Lymington SO41 3YL United Kingdom

Mobile: 01590 613600 Telephone: 01590 613600

AB Inflatables - 10 UL

£ 4,470



Description

AB Inflatables Lammina 10 UL - ORCA CSM / Hypalon Extremely light in weight, small but powerful, designed to deliver performance in style. Built with the same quality standards as our larger, luxury models, the Lammina UL is our most sophisticated lightweight tender yet. Created to deliver performance on the water, its open design also creates an interior that is ideal for safely transporting cargo and crew. Ideal for the cruising couple, this tender feature an ultra-lightweight aluminum hull and a stronger CSM Coated Fabric in 820 D-tex which means a higher level of resistance. Its smaller size is perfect for weaving through crowded moorings and exploring shallow bays. When the day's adventure is over, the Lammina UL's davit lifting points make for easier deck storage. Although the tender is uncoated for minimal maintenance, you can choose to add a Chrome-free Pretreatment and Powder Coating. The UL line hulls are manufactured with key reinforcement points. These include lifting and towing eyes vertically positioned to avoid these from bending and reinforced transom knees. Features: Large Square Transom Alum. Reinforced Base More Payload capacity Ultra High Quality Welding Reinforced Aluminum Bow Eye with SS Rings Reinforced Aluminum Lifting Eyes with SS Rings Aluminum Removable Rowing Seat ORCA (CSM) Coated Fabric Sunbrella Fabric Dinghy Chap Available Sunbrella Fabric Boat Cover Available Internal Aluminum Plate with Security Lip Optional New Chrome Free - Advanced Pretreatment and Powder Coating Technology NEW Ultra High Quality Welding Reinforced (CSM) Fabric Handles Custom Colors Upon Request Non-skid Rubber Floor Specifications: Overall length: 10' / 3.05m Overall Beam: 5'6" / 1.68m Inside Length: 7'2" / 2.18m Inside Beam: 2'8" / 0.81m Tube Diameter: 17" / 0.43m Number of Chambers: 3 Person Capacity: 5 Weight: 95lb / 43kg Recommended HP: 8hp / 6kw Maximum HP: 15hp / 11kw Shaft length: 15" / 38.1dm RDC Design Category: C Hull Thickness 0.125 in / 3.18 mm Standard Equipment: Shallow "V" Marine Grade Aluminum Hull Transom Knee Non-Skid Rubber Floor Panels Plastic External Transom Plate Aluminum Internal Transom Plate With Security Lip Aluminum Bow Eye 3 Aluminum Davit Lifting Points Deck Drain with Plug Orca (CSM) Five Layer Coated Fabric Raised Single Rub Rail Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes Removable Rowing Seat Oarlock Base Telescopic Oars with Aluminum Shaft Paddle Holders Hand Pump Maintenance Kit Owner's Manual 3 Layers Reinforced Seams

Sales status: availableManufacturer: AB InflatablesModel: 10 ULYear built: 2022Length (m): 3.05Weight dry: 43No. of air chambers: 3Persons max: 5Condition: NewSale Type: NewPower: 15Motor: 11Material hull: Aluminium